

Green Certified Products

Fire Safe Compliant

POLISHED CONCRETE & FLOOR CARE

Ivan Imerman Director ivan@ibssales.com.au

PHONE: (02) 8338 0000 MOBILE: 0403 046 038

ADDRESS: 20 Sir Joseph Banks St Botany 2019 OPEN Mon - Fri 8am-4pm

POSTAL: PO Box 6132 Alexandria NSW 2015



Importers and sales of TERRCO grinders – Certi-Shine polished concrete system Vexcon densifiers & sealers – Tough Grip and Shower Grip non-slip sealers Multi-Clean sealers, strippers & cleaners – RJSC sealers – PADCO applicators Polished Concrete Showroom OPEN Mon to Fri 8.30 to 3.30pm

www.polishedconcrete.net.au Member of Master Builders Association: 3012217



Multi-Clean'

Maintenance program for hard surfaces sealed with *Multi-Clean* PREMIER sealer

Daily program

Always remove spills when they happen.

Door entrances should have carpets in place to stop dirt from coming in.

Soils to be removed daily with a dust sweeper.

When using vacuum, make sure the base plate is plastic, NOT metal

Weekly program

Scrub floors with an auto scrubber using a 'white' or 'champagne' pad, or clean using a mop and bucket.

Use Multi-Clean Tough Green, our 'green' cleaner, in your auto scrubber, or mop application for daily cleaning.

Monthly program

After the floor has been cleaned and is dry:

Spray buff with Multi Clean RSB Restorer to remove scratches when they occur using a high speed burnisher with a champagne pad or an ultra high speed blue pad. The Multi Clean RSB Restorer is diluted with 70% water and used as a spray buff to rejuvenate the floor and remove small scratches.

<u>Commercial floors</u> need more regular re-coating over time in high traffic areas so at the same time you then spray buff with Multi Clean Premier (do not dilute) thereafter using a high speed burnisher and a high speed blue pad.

The floor should be recoated in high traffic areas as and when required. A good maintenance program will save you stripping and resealing the floor.

<u>DO NOT</u> clean with CITRUS, AMMONIA, PEROXIDE, CHLORINE or ACID based cleaners. Do NOT use an auto scrubber fitted with a tynex brush. <u>www.polishedconcrete.net.au</u>